

Nominal Diameter



7,2 = 40 mm²

RECTUS Series

26KA

**Technical Description**

European standard industrial profile. Universal brass coupling. Small mass size. Ergonomic sleeve design prevents dirt on the valve body. Series 26 plugs in brass. Series 25 steel plugs recommended for oscillating forces.

Chart**Advantages**

Single handed operation.
European standard.

Interchangeability

RECTUS 25
RECTUS 1600/1625
TEMA 1600
CEJN 320
JWL 520 + JWL 530
and various German products

Material**Coupling**

Back Body
Valve Body
Sleeve
Valve
Spring and Locking Ring
Locking Pins
Seals

Plug

Plug

Working Pressure

PB = 35 bar, maximum
static working pressure with
safety factor of 4 to 1.

Working Temperature*


-20°C up to +100°C (NBR)
-40°C up to +120/150°C (EPDM)
-15°C up to +200°C (FKM)
depending on the medium.

*At a temperature below
-20°C and above +100°C
special seals are available on
request.

Standard


Brass
Brass
Thermoplastic
Brass
AISI 301
AISI 420
NBR

Brass

Plugs**RECTUS Series 26KA**


Hose Barb

| Connection A | Hex SW | L mm | D mm | L1 mm | L2 mm | Hex1 SW1 | B mm | G mm | Version | Part Number | DS |
|--------------|--------|------|------|-------|-------|----------|------|------|----------|---------------|----|
| 6 mm | | 48 | 12 | 25 | | | | | Standard | 26SF TF06 MXX | ■ |
| 8 mm | | 48 | 12 | 25 | | | | | Standard | 26SF TF08 MXX | ■ |
| 9 mm | | 48 | 12 | 25 | | | | | Standard | 26SF TF09 MXX | ■ |

Plugs**RECTUS Series 26KA**

Male Thread

| Connection A | Hex SW | L mm | D mm | L1 mm | L2 mm | Hex1 SW1 | B mm | G mm | Version | Part Number | DS |
|--------------|--------|------|------|-------|-------|----------|------|------|----------|---------------|----|
| G 1/4 | 17 | 33 | | 9 | | | | | Standard | 26SF AW13 MXX | ■ |
| G 3/8 | 19 | 33 | | 9 | | | | | Standard | 26SF AW17 MXX | ■ |
| G 1/4 | 17 | 33 | | 10 | | | | | Standard | 26SF IW13 MXX | ■ |
| G 3/8 | 19 | 33 | | 10 | | | | | Standard | 26SF IW17 MXX | ■ |



Female Thread

DS = Delivery Status: ■ in stock □ on short call □ medium term delivery

Couplings**RECTUS Series 26KA**

| | Connection A | Hex SW | L mm | D mm | L1 mm | L2 mm | Hex1 mm | B mm | G mm | Version | Part Number | DS |
|-------------------|--------------|--------|------|------|-------|-------|---------|------|------|----------|-------------------|----|
| Male Thread | G 1/4 | 22 | 39 | 25 | 9 | | | | | Standard | 26KA AW13 MPXS_99 | ■ |
| | G 3/8 | 22 | 41 | 25 | 9 | | | | | Standard | 26KA AW17 MPXS_99 | ■ |
| | G 1/2 | 22 | 44 | 25 | 12 | | | | | Standard | 26KA AW21 MPXS_99 | ■ |
| Female Thread | G 1/4 | 22 | 41 | 25 | 9 | | | | | Standard | 26KA IW13 MPXS_99 | ■ |
| | G 1/2 | 24 | 44 | 25 | 10 | | | | | Standard | 26KA IW21 MPXS_99 | ■ |
| Hose Barb | 6 mm | 21 | 58 | 25 | 25 | | | | | Standard | 26KA TF06 MPXS_99 | ■ |
| | 8 mm | 21 | 58 | 25 | 25 | | | | | Standard | 26KA TF08 MPXS_99 | ■ |
| | 9 mm | 21 | 58 | 25 | 25 | | | | | Standard | 26KA TF09 MPXS_99 | ■ |

DS = Delivery Status: ■ in stock □ on short call □ medium term delivery