

> Home UK & Ireland > Loctite > Product Search > Full Product List Loctite

[Back to Overview](#)



## Loctite® 542

Thread sealant for fine metal threaded fittings as used in hydraulic and pneumatic installations, and small fittings in general. Approvals; DVGW approval (Reg.No.NG-5146 AR 0855) ; tested acc. to EN 751-1 description: curable, liquid maximum thread size: 3/4 temperature resistance: +150 °C disassembly strength: medium substrate to be sealed: Metal

### Technical Information

<b>Applications</b>	Adhesives Sealants Sealants > Industrial Sealants Adhesives > Industrial Bonding Adhesives > Thread Sealing Thread Sealing and Threadlocking > Thread Sealing
<b>Chemistry</b>	(Meth-)Acrylates (monomeric)
<b>Media Carrier</b>	100 % liquid & paste
<b>Temperature range</b>	-55°C - +150°C
<b>Cure Type</b>	Anaerobic
<b>RoHS Compliant</b>	Contact Henkel
<b>Product Documents</b>	
MSDS Documents	<a href="#">PDF</a> English
TDS Documents	<a href="#">PDF</a> English

© 2009 Henkel Ltd., Hatfield | [Locations](#) | [Terms of Use](#) | [Credits](#) | [Privacy Policy](#)